

EAZY - 44

Single Swing Door

OZHN-DP-
PR-33 4M ABM



OZHN-I10MM 3M BM
OZHN-I12MM 3M BM
Profile-GTG-180



OFS-ACC-GDP STD
BM X 1 Nos.
Top Pivot for Patch/
Point Fitting Doors



OZHN-DP1-CC
STD MILL x2 Nos.
Corner Cleat



OPF-2 STD BM
X 1Nos.
Top Patch



OZHN-DP3 3M
ABM
Door Profile



OGH-11 25x450MM
BM
Glass Door Handle

OPF-3 STD
BM X 1 Nos.
Bottom Patch



FS-8400-S STD BM
X 1Nos.
Floor Spring



OPL-1 STD BM
X 1Nos.
Corner Patch Lock
with Strike Plate




OZHN-L10MM 3M BM
OZHN-L12MM 3M BM
L Profile-GTG-90




Refer to the Ozone glass hardware range for more choices

TYPICAL LAYOUT


OPF-2 STD BM
X 1Nos.




OFS-ACC-GDP
STD
BM X 1 Nos.




OZHN-DP1-CC
STD MILL x2 Nos.
Corner Cleat




OZHN-I10MM 3M BM
OZHN-I12MM 3M BM
L Profile-GTG-90



OZHN-DP-PR-33
4M ABM




OZHN-DP3 3M
ABM
Top Patch




OGH-11
25x450MM BM
Glass Door Handle




FS-8400-S STD BM
X 1Nos.



OPF-3 STD
BM X 1 Nos.



OPL-1 STD BM
X 1Nos.



Technical Specification

Glass Type	Tempered Glass
Glass Thickness	10-12mm
Max. Door Height	3000mm
Max. Partition Height	3000mm
Door Weight	45-80kg
Application	Door assembly with Over Panel and Sidelight
Material	Aluminium

Note: The number of the profiles may change as per actual site measurement.